

## Hawkeye® Q2 Video Borescope Specifications

Diameter	2.8 (.110") (+.1mm/-0mm) 3.9, and 6.0mm (.154, and .236" )
Lengths	2.8mm: 1meter (3'3"), 2meter (6'6") 3.9mm: 1.5meter (4'11"), 3meter (9'10") * 6mm: 1.5meter (4'11"), 3meter (9'10"), 6.0meter (19'6"), 7.5meter (24'6")
Articulation	1.0 - 2.0m length: +/- 110° min. (+/- 10°) 1.5 - 3.0m length: +/- 140° min. (+/- 10°) 6.0m length: +/- 100° min. (+/- 10°) 7.5m length: +/- 90° min. (+/- 10°)
Field-of-View	80° Diagonal +/- 10° **
Depth-of-Field	2.8mm OD: 2.5mm - infinity 3.9 and 6.0mm OD: 8mm - infinity***
Direction-of-View	0° 90° **** 0 & 90° (Dual View)
Sheath	Tungsten Braid
Illumination	Integrated White LED
Display	5" HD Display
Camera	2.8mm: 960x720p Color Camera 3.9, 4.5 and 6mm: 1MP Color CMOS
Interfaces	HDMI, USB, Micro-SD
Battery	4 hr. run time, Rechargeable Li-Ion

---

Recording Media	Micro-SD Card
Digital Photo Format	JPEG
Video Format	MPEG 4
Operating Temp. Range	Probe: - 20 to +60C (-4 to +140 F) : Display Unit: -10to +50C (14 to +122F)
Storage Temp. Range	- 20 to + 60 C (-4 to +140 F)
Weight	2.2LB
Environmental	Sheath: IP67 Host: IP54

---

Note

- \* Longer lengths available upon request.
- \*\* Custom FOV available upon request.
- \*\*\* Custom Depth of Field available upon request
- \*\*\*\* Dedicated 90° are available upon request.

Please contact our sales team at 585-235-2620 for more information.