

Hawkeye® Q2 Micro Video Borescope Specifications

Diameter	.95mm (.037") (+0.1mm/-0mm)
	1.2mm (.047") (+0.1mm/-0mm)
	1.85mm (.07") (+0.1mm/-0mm)
	2.0mm (.073") (+0.1mm/-0mm)
Lengths	1.0 meter (3'3")
	1.5 meter (4'11")
Articulation	N/A
Field-of-View	110° Diagonal +/- 10°
Depth-of-Field	1.5mm - 20mm
Direction-of-View	.95 and 1.2mm 0°
	1.85mm 0°
	2.0mm 0 and 90°
Sheath	.95mm: Polyimide w/ SS Mesh Underlayer*
	1.85 and 2.0mm: Multi Layer Tungsten

Illumination	Integrated White LED .95mm: Rear 1.2mm, 1.85 and 2.0mm: Front
Display	5" HD Display
Camera	.95 and 1.2mm: 160,000 pixel Color CMOS 1.8 and 2.0mm: 520,000 pixel Color CMOS
Interfaces	HDMI, USB, Micro-SD
Battery	4 hr. run time, Rechargeable Li-Ion
Recording Media	Micro-SD Card
Digital Photo Format	JPEG
Video Format	MPEG 4
Operating Temp. Range	Probe: - 20 to +60C (-4 to +140 F) : Display Unit: -10to +50C (14 to +122F)
Storage Temp. Range	- 20 to + 60 C (-4 to +140 F)

Weight	2.2LB
Environmental	Sheath: IP67 Host: IP54
Note	*Ultra Flexible Stainless Steel Spring Coil Available Upon Request (Splash Resistant) Please contact our sales team at 585-235-2620 for more information.